

**Appln No. 10/816,650**  
**Amdt date November 28, 2005**  
**Reply to Office action of October 4, 2005**

**Amendments to the Specification:**

Please amend the specification as follows:

(1) On page 2, line 31, after "of the present invention;", please add the following new paragraph:

--FIG. 2c is a perspective view of the scoop of FIG. 2b mounted to a triangular notch recess located on an enclosure:--

(2) At the top of page 6, before the first sentence beginning with "FIG. 3 is a detail...", please add the following new paragraph:

--FIG. 2c is a perspective view of the scoop 250 of FIG. 2b mounted to a triangular notch recess 119 located on the enclosure 102. More specifically, the triangular hook portion 254 comprises two side surfaces that are non-parallel (i.e., tapered similar to two sides of a triangle) at the end of the handle portion 262. With reference to FIG. 2, the enclosure 102 incorporates a triangular notched recess 119 having a corresponding shape as the triangular hook portion 254 on the scoop 250. The tapered surfaces of the hook portion 254 on the scoop mate with the tapered sides on the triangular notched recess 119 on the enclosure 102 to form a gravity lock preventing the hook from sliding out of the notched recess. To remove the scoop 250 from the enclosure 102, the scoop 250 needs to be lifted so that the hook disengages from the notched recess.--